



C61

Mobile Computer



Android



4G



Wi-Fi



Bluetooth



1D Barcode



2D Barcode



NFC



UHF



Camera



GPS

Chainway C61 is a new generation rugged handheld computer with robust performance. Built with Android 11/13 OS and Octa-Core processor, it supports 27 keys / 37 keys / 47 keys optional keypad, abundant accessories like trigger handle, and features powerful removable battery. And it delivers optional barcode scanning, RFID, NFC, etc. This mobile computer can fulfill applications in logistics, warehousing, retail, etc.



Specification

Physical Characteristics

Dimensions	202.0 x 72.5 x 32.0mm / 7.95 x 2.85 x 1.26in. (Device Weight for Argentina, Uruguay, Bolivia, Ecuador market: 342*404g, including battery)
Weight	370g / 13.05oz. (SE4710) ; 404g / 14.25oz. (SE4850) / 26 .05oz. / 738g (SE4850, UHF, pistol battery)
Keypad	Main keyboard (Optional) : 27 keys / 37 keys / 47 keys; Side keys: 2 scan keys + 2 volume keys + 1 user-defined key
Battery	6700 mAh removable main battery, 5200 mAh optional pistol battery, support QC3.0 and RTC; Built in 100mAh backup battery, supporting battery hot swap, improving reliability and ensuring user data security Standby: up to 680 hours (only main battery ; WiFi: up to 560h; 4G: up to 560h) Continuous use: over 12 hours (depending on user environment) Charging time: 3.5 hours (charge device by standard adaptor and USB cable)
Display	4-inch high definition display, 800*480
Touch Panel	Multi-touch panel, gloves and wet hands supported
Sensor	Accelerometer sensor, light sensor, proximity sensor, gravity sensor
Notification	Sound, LED indicator, vibrator
Audio	2 microphones, 1 for noise cancellation; 2 speakers; receiver
Card slot	1 slot for Micro SIM card, 1 slot for TF card
Interfaces	USB Type-C, USB 3.1, OTG, extended thimble

Performance

CPU	Octa-core, 2.0 GHz
RAM+ROM	3GB + 32GB / 4GB + 64GB
Expansion	Supports up to 256GB Micro SD (TF) card

Developing Environment

Operating System	Android 11/13; GMS, 90-day security updates, Android Enterprise Recommended, Zero-Touch, FOTA, Soti MobiControl, SafeUEM supported. Committed support for a future upgrade to Android 18 pending feasibility
SDK	Chainway Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

User Environment

Operating Temp.	-4°F to 122°F / -20°C to 50°C
Storage Temp.	-40°F to 158°F / -40°C to 70°C
Humidity	5% RH to 95% RH (non condensing)
Drop Specification	Multiple 1.8 m / 5.9 ft. drops (at least 20 times) to the concrete across the operating temperature range
Tumble Specification	1000 x 0.5 m / 1.64 ft. falls at room temperature
Sealing	IP65 per IEC sealing specifications
ESD	±15 KV air discharge, ±8 KV conductive discharge

Communication

WLAN	Support 802.11 a/b/g/n/ac/ax-ready/d/e/h/i/k/r/v, 2.4G/5G dual-band, IPV4, IPV6, 5G PA; Fast roaming: PMKID caching, 802.11r, OKC Operating Channels: 2.4G(channel 1~13), 5G(channel 36,40,44,48,52,56,60,64,100,104,108,112,116,120,124,128,132,136,140,144,149,153,157,161,165), Depends on local regulations Security and Encryption: WEP, WPA/WPA2-PSK(TKIP and AES), WAPI-PSK—EAP-TTLS, EAP-TLS, PEAP-MSCHAPv2, PEAP-LTS, PEAP-GTC, WPA3-Enterprise,etc.
-------------	--

Vo-LTE	Support Vo-LTE HD video voice call
Bluetooth	Bluetooth 5.1
GNSS	GPS/AGPS, GLONASS, BeiDou, Galileo, internal antenna 2G: 850/900/1800/1900 MHz 3G: CDMA EVDO: BC0 WCDMA: 850/900/1900/2100 MHz TD-SCDMA: A/F(B34/B39) 4G: B1/B3/B5/B7/B8/B20/B38/B39/B40/B41
WWAN (Europe, Asia)	2G: 850/900/1800/1900MHz 3G: 850/900/1900/2100MHz 4G: Android 11: B2/B4/B5/B7/B8/B12/B13/B17/B28A/B28B/B38
WWAN(America)	

Data Collection

Camera

Rear Camera	Rear 13 MP Autofocus with flash
--------------------	---------------------------------

NFC

Frequency	13.56 MHz
Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
Chips	M1 card (S50, S70), CPU card, NFC tags, etc.
Range	2-4 cm

UHF (Optional)

Engine	CM710-1 module based on Impinj E710 CM2000-1 module based on Impinj Indy R2000
Frequency	865-868 MHz / 920-925 MHz / 902-928 MHz
Protocol	EPC C1 GEN2 / ISO18000-6C
Antenna	Circular Polarized Antenna (4 dBi)
Power	1W (30 dBm, +5 dBm to +30 dBm adjustable) 2W Optional (33 dBm, for Latin America, etc.)
Max Read Range	Impinj E710 chip: 27m (Impinj MR6 tag, size70 x 15mm) 26m (Impinj M750 tag, size70 x 15mm) 30m (Alien H3 Anti-Metal tag, size 130 x 42mm) Impinj R2000 chip: 22m (Impinj MR6 tag, size 70 x 15mm) 24m (Impinj M750 tag, size 70 x 15mm) 29m (Alien H3 Anti-Metal tag, size 130 x 42mm)
Fastest Read Rate	1300+ tags/sec
Communication Mode	Pin Connector

* Ranges are measured in the open outdoors and low interference environment, and rate is measured in a laboratory low interference environment, they are affected by tags and environment.

Barcode Scanning (optional)

2D Scanner	Zebra: SE4710/SE4750SR/SE4750MR/SE4750DP/SE4850; Honeywell: N6603/EX30
1D Symbolologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Symbolologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.

Optional accessories(See details in Accessory Guide)

Separate handle with one button, Wrist Strap; Charging Cradle

Handle + battery (handle battery 5200 mAh, one button)

UHF back clip + handle (5200 mAh, one button)

Notice: Product specifications are subject to change without prior notice. / Model: C61 / Update Date: 2024-06-28

CHAINWAY®

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: http://www.chainway.net