CHAINWAY®



C70

Thermometry Mobile Data Terminal



















Android

4G

WiFi

Bluetooth

1D Barcode

2D Barcode

NFC

Camera

GPS

Chainway C70 is a high-performance intelligent handheld terminal which designed for temperature measurement. It is developed based on Android system, with high-performance processor, first-class configuration and fast operation, this device can be widely used in multiple temperature measurement scenarios. Temperature measurement module on top is more convenient for the user to operate, and helps the user to quickly realize information management and improve work efficiency.



Specification

| Performance | |
|------------------|---|
| CPU | Cortex-A53 2.3 GHz Octa-core |
| RAM+ROM | 3GB+32GB / 4GB+64GB |
| Expansion | Supports up to 128 GB Micro SD card |
| Operating System | Android 11; SafeUEM supported. Committed support for a future upgrade to Android 12, 13, and Android 14 pending feasibility |

| | reasibility |
|---------------|--|
| Communication | |
| WLAN | IEEE802.11 a/b/g/n/ac, 2.4G/5G dual-band, internal antenna |
| WWAN | 2G: GSM850/GSM900/DCS1800/PCS1900 |
| | 3G: WCDMA: B1/B2/B4/B5/B8 CDMA2000 EVDO: BC0 TD-SCDMA: A/F |
| | 4G: B1/B2/B3/B4/B5/B7/B8/B12/B17/B20/B28A/B28B/ B34/B38/B39/B40/B41 |
| Bluetooth | Bluetooth 5.0 |
| GNSS | GPS/AGPS, GLONASS, BeiDou; internal antenna |

| Physical Characteristics | |
|--------------------------|--|
| Dimensions | 163.8 x 79.2 x 13.8 mm / 6.45 x 3.12 x 0.54 in. |
| Weight | 242g / 8.5oz. |
| Display | 5.2" IPS LTPS 1920 x 1080 |
| Touch Panel | Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported |
| Expansion Slot | 1 slot for Nano SIM card, 1 slot for Nano SIM or TF card |
| Interfaces | USB2.0 Type-C, OTG, supports TypeC headphones |
| Sensors | Light sensor, proximity sensor, gravity sensor |
| Notification | Sound, LED indicator, vibrator |
| Audio | 2 microphones, 1 for noise cancellation; 1 speaker; receiver |
| Keypad | 4 front keys, 1 power key, 2 scan keys, 1 multifunctional key |
| Power | Main battery: Li-ion, rechargeable, 4000mAh |
| | Standby: over 300 hours |
| | Continuous use: over 12 hours (depending on user environment) |
| | Charging time: 2-3 hours (with standard adaptor and USB |

| Developing Environment | |
|------------------------|--------------------------|
| SDK | Software Development Kit |
| Language | Java |
| Tool | Eclipse / Android Studio |

| User Environment | |
|-------------------|---|
| Operating Temp. | -4°F to 122°F / -20°C to 50°C |
| Storage Temp. | -40°F to 158°F / -40°C to 70°C |
| Humidity | 5%RH - 95%RH non condensing |
| Dran Englisherian | Multiple 1.8m / 5.9ft drops (at least 20 times) to the concrete |

| Drop Specification | across the operating temperature range |
|----------------------|--|
| Tumble Specification | 1000 x 0.5m/1.6ft falls at room temperature |
| Sealing | IP65 / IP67 per IEC sealing specifications |
| ESD | ±15KV air discharge, ±6KV conductive discharge |

Data Collection

| Temperature Collection | |
|------------------------|--|
| Measure Position | Human forehead / Object surface |
| Measure Method | Non-contact / Infrared |
| Measure Distance | 1-3 cm |
| Measure Range | Human forehead: 32°C to 42.9°C; Object surface: -40°C to 115°C; |
| Measure Accuracy | Human forehead: ±0.2°C; Object surface: ±0.5°C; |
| Measure Duration | 1 sec |
| Spectral Range | 5.5 -15 μm |
| Resolution | 0.02°C |
| ***** | |

 $^{^{*}\}mbox{The}$ infrared module has 80 degrees limitation, the best measure angle should be in this range.

| Camera | |
|--------|--|
|--------|--|

| Rear Camera | 13MP Autofocus with flash |
|----------------------------|---------------------------|
| Front Camera (optional) | 5MP camera |

NFC

| Frequency | 13.56MHz |
|-----------|---|
| Protocol | ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc. |
| Chips | M1 card (S50, S70), CPU card, NFC tags, etc. |
| Range | 2-4cm |

Barcode Scanning (Optional)

| 2D Imager Scanner | Zebra SE4710 / Honeywell N6603 |
|-------------------|---|
| 1D Symbologies | UPC/EAN, Code128, Code39, Code93, Code11, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, MSI, RSS, etc. |
| 2D Symbologies | PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc. |

Accessories(See details in Accessory Guide)











Cradle (Optional)



Holster(Optional)

Notice: Product specifications are subject to change without prior notice. / Model: C70 / Update Date: 2022-12-2